

Model		SDJA500	SDJA1000	SDJA1500
Load capacity/rated load	Q(kg)	500	1000	1500
Load centre distance	c(mm)	500	500	500
Fork height, lowered	h_{13} (mm)	90	90	90
Height, mast lowered	h_1 (mm)	2000	2085/1840	2090
Max. lift height	h_3 (mm)	1600	1600/2500	1600
Height, mast extended	h_4 (mm)	2010	2165/2925	2150
Overall length	l_1 (mm)	1380/1640	1380/1640	1380/1640
Overall width	b_1 (mm)	805	1000/750	1000
Fork dimensions	s/e/l(mm)	48/100/800(1060)	30/100/800(1060)	30/100/800(1060)
Width overall forks	b_5 (mm)	200-745	200-950/700	200-950
Ground clearance, laden, below mast	m_1 (mm)	20	25	25
Aisle width for pallets 1000x1200 crossways	A_{st} (mm)	1915	1915	1915
Aisle width for pallets 800x1200 lengthways	A_{st} (mm)	1910	-	-
Turning radius	W_a (mm)	1235	1235	1235
Lift speed,laden/unladen	mm/time	25	25	21
Lowering speed,laden/unladen	mm/s	Manual control	Manual control	Manual control
Service weight	kg	161	250/316	280

